

VALQUA BONDED GATE SEAL

~Ultimate transfer gate valve seal~



Feature and Application

Seal Material	Color	Main Application	Feature
ULTIC ARMOR	Transparent Amber	CVD	High purity Particle free No metal to metal contact Eliminated exposure surface of seal material to plasma
FLID	Black	PVD, Loadlock gate	Abrasion resistance No metal to metal contact Eliminated exposure surface of seal material to plasma


Example of Actual Equipment Evaluation

Equipment: PVD
Location: Gate Gas: N₂, Ar
Temp.: R.T. Wafer count: Approx.15,000


Fluoro rubber O-ring



Entire view




Twisting



Metal contacting scar

ULTIC ARMOR BONDED GATE SEAL



Entire view



No twisting and metal contacting scar



VALQUA KOREA Co., Ltd.

Seal Material Information




Figure 1. Metal components content




Figure 2. The amount of desorbed TOC

All trademarks and registered trademarks noted in this file are the exclusive property of Nippon Valqua Industries, Ltd. unless otherwise specified. This document is made for use in Japan. Although these data are created based on the data and the information of February 2009, Nippon Valqua Industries Ltd. may change these data without notice for the reason of improvement in functional of a product, standard revision and others. Please note the following point in use of these data. (1) An operating temperature, pressure range, durability, etc. indicated in this catalogue do not assume each operation conditions but show the application possibility based on our company data, an actual result, etc. Therefore, please use these data after checking the aptitude in actual use environment. (2) The data contained within this catalogue can only be taken as a guide. (3) A standard, a value, etc. are the purposes made legible, and may be performing an extract, recombination, arrangement, conversion, etc. of a value. (4) Although the maximum attention was paid in this data creation, Nippon Valqua Industries Ltd. will not accept responsibility for any loss incurred through error or omission. Please contact your distributor or VALQUA group if you have any questions. (5) This document contains confidential information. So please do not disclose this confidential information to the third party without our company's permission.

© 2009 Nippon Valqua Industries, Ltd. All rights reserved.
Manufactured in Japan.



VALQUA KOREA Co., Ltd.
<http://www.valqua.kr>

Contact:

VALQUA KOREA Co., Ltd.
Bookook Securities B/D#602, 34-2 Yeuido-Dong,
Yeongdeungpo-Gu, Seoul, Korea (150-995)
Tel: +82-2-786-6718, Fax: +82-2-786-6719